

OPT MTA

60

CR/

≥83

STRIP-60 Flexible LED Strip



Description

Introducing STRIP-60 LED strip lighting system. STRIP-60 offers new possibilities in the way we illuminate areas and surfaces. The secret lies in its thin and flexible PCB, which allows for long and linear lengths to be preformed with ease. With added advantages of low wattage and uniform lighting the STRIP-60 opens the area for many design concepts to become reality.



Specification Features

Colours:7 colour options availableLight Source:3528 SMD LEDLED Type:Epistar (Taiwan)Colour Temperature (K):3200K, 4000K, 6500KColour Rendering Index:≥83Colours: (wave length)(B) 465nm, (G) 525nm, (R) 625nm, (O) 600nmNumber of LED per mtr:60Wattage Per MTR (W):4.8WInput Voltage (VDC):12VDCBeam angle (o):1200Wiring:ParallelIP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting profile***		
LED Type:Epistar (Taiwan)Colour Temperature (K):3200K, 4000K, 6500KColour Rendering Index:≥83Colours: (wave length)(B) 465nm, (G) 525nm, (R) 625nm, (O) 600nmNumber of LED per mtr:60Wattage Per MTR (W):4.8WInput Voltage (VDC):12VDCBeam angle (o):1200Wiring:ParallelIP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	Colours:	7 colour options available
Colour Temperature (K):3200K, 4000K, 6500KColour Rendering Index:≥83Colours: (wave length)(B) 465nm, (G) 525nm, (R) 625nm, (O) 600nmNumber of LED per mtr:60Wattage Per MTR (W):4.8WInput Voltage (VDC):12VDCBeam angle (o):1200Wiring:ParallelIP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	Light Source:	3528 SMD LED
Colour Rendering Index: ≥ 83 Colours: (wave length)(B) 465nm, (G) 525nm, (R) 625nm, (O) 600nmNumber of LED per mtr: 60 Wattage Per MTR (W): $4.8W$ Input Voltage (VDC): $12VDC$ Beam angle (o): 1200 Wiring:ParallelIP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires: $12VDC$ constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	LED Type:	Epistar (Taiwan)
Colours: (wave length)(B) 465nm, (G) 525nm, (R) 625nm, (O) 600nmNumber of LED per mtr:60Wattage Per MTR (W):4.8WInput Voltage (VDC):12VDCBeam angle (o):1200Wiring:ParallelIP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	Colour Temperature (K):	3200K, 4000K, 6500K
(R) 625nm, (O) 600nmNumber of LED per mtr:60Wattage Per MTR (W):4.8WInput Voltage (VDC):12VDCBeam angle (o):120oWiring:ParallelIP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	Colour Rendering Index:	≥83
Number of LED per mtr:60Wattage Per MTR (W):4.8WInput Voltage (VDC):12VDCBeam angle (o):120oWiring:ParallelIP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	Colours: (wave length)	(B) 465nm, (G) 525nm,
Wattage Per MTR (W):4.8WInput Voltage (VDC):12VDCBeam angle (o):120oWiring:ParallelIP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:0ptional aluminium mounting		(R) 625nm, (O) 600nm
Input Voltage (VDC):12VDCBeam angle (o):120oWiring:ParallelIP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	Number of LED per mtr:	60
Beam angle (o):120oWiring:ParallelIP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	Wattage Per MTR (W):	4.8W
Wiring:ParallelIP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	Input Voltage (VDC):	12VDC
IP Rating:IP20Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	Beam angle (o):	1200
Cutting Increments/Sections:50mm (groups of 3 LED)Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	Wiring:	Parallel
Requires:12VDC constant voltage driverDimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	IP Rating:	IP20
Dimmable:Yes* DALI, 0-10V, DMX-512, RFIES files:Yes**Mounting:Optional aluminium mounting	Cutting Increments/Sections:	50mm (groups of 3 LED)
IES files: Yes** Mounting: Optional aluminium mounting	Requires:	12VDC constant voltage driver
Mounting: Optional aluminium mounting	Dimmable:	Yes* DALI, 0-10V, DMX-512, RF
	IES files:	Yes**
	Mounting:	

* For dimming options please refer to the controller section for further details.

** Available upon request.

*** Mounting profile optional (not required)

Diagrams / Additional



Order Info

	Colour Temp: Order Code: Product Code: Lumens/m:	6500K 20010 STRIP-60-65K 442 lm/m
	Colour Temp: Order Code: Product Code: Lumens/m:	4000K 20009 STRIP-60-40K 436 lm/m
	Colour Temp: Order Code: Product Code: Lumens/m:	3200K 20011 STRIP-60-32K 420 lm/m
	Colour Temp: Order Code: Product Code: Lumens/m:	625nm 20014 STRIP-60-RED 126 lm/m
	Colour Temp: Order Code: Product Code: Lumens/m:	525nm 20013 STRIP-60-GREEN 234 lm/m
	Colour Temp: Order Code: Product Code: Lumens/m:	465nm 20012 STRIP-60-BLUE 90 Im/m
	Colour Temp: Order Code: Product Code: Lumens/m:	600nm 20015 STRIP-60-ORANGE 48 lm/m
4	50mm	
	+	R3 0 19
3mm		

Domus Lighting 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: sales@domuslighting.com Specification subject to change without prior notice.