

## STRIP-60-WP Image: Strip Im

## Description

Introducing STRIP-60-WP LED strip lighting system. STRIP-60-WP weatherproof offers new possibilities in the way we illuminate areas and surfaces. Ideal for areas of dampness or high humidity. The secret lies in its thin and flexible PCB which is encapsulated in special silicon U-channel with silicon overlay. With added advantages of low wattage and uniform lighting the STRIP-60-WP enables many design concepts to become reality. Design usages include under kitchen cupboards, laundries, bathroom and exterior applications.



Order Info

## **Specification Features**

specification reactives				
Colours: Light Source: LED Type: Colour Temperature (K):	5 colour options available 3528 SMD LED Chimel (Taiwan) 3200K, 6500K		Colour Temp: Order Code: Product Code: Lumens/m:	6500K 20050 STRIP-60-WP-65K 480 lm/m
Colour Rendering Index: Colours (wave length): Number of LED per mtr: Wattage Per MTR (W): Input Voltage (VDC):	≥80 (B) 465nm (R) 625nm (G) 525nm 60 4.8W 12VDC		Colour Temp: Order Code: Product Code: Lumens/m:	3200K 20051 STRIP-60-WP-32K 420 lm/m
Beam angle (°): Wiring: IP Rating: Cutting Increments/Sections: Requires:	120° Parallel IP66* 50mm (group of 3 LED) 12VDC constant voltage driver		Colour: Order Code: Product Code: Lumens/m:	Blue 20052 STRIP-60-WP-BLUE 90 lm/m
Dimmable: IES files: Mounting: * Not suitable for underwater app.	Yes** DALI, 0-10V, DMX-512, RF Yes*** Optional aluminium mounting profile****		Colour: Order Code: Product Code: Lumens/m:	Green 20053 STRIP-60-WP-GREEN 348 Im/m

\*\*\* Available upon request.

\*\*\*\*Mounting profile optional (not included).



Colour: Red Order Code: 20054 Product Code: STRP-60-WP-RED Lumens/m: 126 lm/m

## Diagrams / Additional





Domus Lighting 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: sales@domuslighting.com Specification subject to change without prior notice.