

## PANEL-312 Panel Light



## Description

45W LED Panel light. Natural anodised aluminium frame, opal diffuser. These are ideal as ceiling light for T-Bar ceilings, or by using a plaster recessed frame, ideal for commercial applications such as office spaces. Fully dimmable with Domus dimmer series.



## **Specification Features**

Input Voltage:	240VAC	
Power (W):	45W	
IP rating (IP):	44	
Lumens (lm):	Warm White 3000K - 2950lm Neutral White 4000K - 3000lm White 6000K - 3050lm	
LED type:	High efficiency SMD LED	
CCT:	3000К -4000К - 6000К	
CRI:	≥80	
Dimmable:	Yes*	
Mounting Type:	Recessed into standard grid ceiling or via optional plaster trim kit for plaster board ceilings or via optional wire suspended or surface mounted kit.	
Lifespan (hrs):	50,000hrs	
Dimensions:	(L) 1195mm x (W) 295mm x (H) 10mm	
* Dimmable when used in conjunction with the Domus dimmer series.		

May work with others but not tested.

## Diagrams / Additional



Order Code: Product Code: Colour:	19311 PANEL-312-SLR-WW Warm White LED 3000K			
Order Code: Product Code: Colour:	19310 PANEL-312-SLR-NW Neutral White LED 4000K			
Order Code: Product Code: Colour:	19309 PANEL-312-SLR-W White LED 6000K			
	$\nearrow$			
LED Panel Trim (Recessed Plaster Frame)				
Product Code:				
Order Code:	19326			
4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	ececece in the			
LED Panel Frame (Surface Mount Frame)				
Product Code:				
Order Code:	19330			
	Aluminium Anodised			

Product Code:	SM-KIT312-W
Order Code:	19334
Colour:	Satin White

Domus 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com Specification subject to change without prior notice.