

ZEKE-9 SQUARE LED Steplight

(3yr) ies (65) out of the contraction of the contra

Description

The surface mounted ZEKE-9-Square features a slim-line, cast-aluminium body with dual cable glands for easy installation. The aluminium trim features a special chromate process before a polyester powder coated finish is applied, for extended wear in harsh external environments. With an IP65 rating, the ZEKE-9-Square features amazing downward illumination with minimal power consumption; A total of 9W of high intensity illumination. Particularly useful for outside entertaining areas, external pathways or any area in which recessed mounting is not an option.



Specification Features

| Input Voltage: | 240V AC |
|-----------------|---|
| Power (W): | 9W |
| IP rating (IP): | IP65 |
| Lumens (lm): | Warm White 3000K - 800lm White 5000K - 900lm |
| LED type: | SMD |
| CCT: | 3000K - 5000K |
| CRI: | ≥85 |
| Beam angle (°): | 120° |
| Dimmable: | No |
| Lifespan (hrs): | 50,000hrs |
| | |

Diagrams / Additional



| Item No. | Variant | Colour |
|----------------|---------|--------|
| ZEKE-9-SQR-BLK | 19516 | 3000K |
| | 19517 | 5000K |
| ZEKE-9-SQR-DGR | 19492 | 3000K |
| | 19493 | 5000K |
| ZEKE-9-SQR-SLR | 19490 | 3000K |
| | 19491 | 5000K |
| ZEKE-9-SQR-WHT | 19508 | 3000K |
| | 19509 | 5000K |

Domus Lighting 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com Specification subject to change without prior notice.