

DEKA Brass Inground Light

(**3yr**)







Description

The DEKA luminaire provides a practical solution for all inground lighting applications including pathways, driveways, courtyards and decks. Utilising a solid brass CNC machined external fascia plate and a 6063 graded aluminium in a black anodised finish.

The DEKA recessed inground luminaire in solid brass finish will age with time. This is a natural process which adds to the overall appeal of the fixture. A polycarbonate housing is provided for concrete applications. For installations in which do not require the polycarbonate housing such as timber decks the stainless steel spring clips offer a secure fit. Idea applications would also include up lighting trees, feature garden wall, external house fascia etc.



Specification Features

Input Voltage:	12V DC	
Power (W):	3W	
IP rating (IP):	65	
Lumens (lm):	Warm White 3000K - 300lm	
	White 5000K - 350lm	
LED type:	CREE	
CCT:	3000K - 5000K	
CRI:	≥83	
Beam angle (°):	60°	
Dimmable:	No	
Lifespan (hrs):	50,000hrs	
Cutout (ø):	Ø77mm	
Drive over:	2000kgs (19438, 19440)	

Diagrams / Additional



Body		
Order Code:	19458	
Product Code:	DEKA-BODY-3K	
Colour:	Warm White - 3000K	
Order Code:	19459	
Product Code:	DEKA-BODY-5K	
Colour:	White - 5000K	

Brass Covers

B1035 COVC15		
	Order Code:	19438
	Product Code:	DEKA-COVER-RND-OPEN-BRS
	Order Code:	19440
	Product Code:	DEKA-COVER-SQR-OPEN-BRS
	Order Code:	19442
	Product Code:	DEKA-COVER-1-WAY-BRS
	Order Code:	19444
	Product Code:	DEKA-COVER-2-WAY-BRS
	Order Code:	19446
	Product Code:	DEKA-COVER-3-WAY-BRS
	Order Code:	19448
	Product Code:	DEKA-COVER-4-WAY-BRS
	Order Code:	19450
	Product Code:	DEKA-COVER-EYELID-BRS

Domus Lighting 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: enquiries@domuslighting.com Specification subject to change without prior notice.