

INTERCEPT® II CEILING FAN



Brushed Aluminium

Installation Locations:

Indoor and outdoor (provided the fan is fully undercover)

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 28°

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Wall Controller Speed Capacitor Values:

3.5µF & 2µF

Top of canopy cover to lowest point of the fan:

Approximately 330mm

Rotational Diameter:

1320mm (52") blade sweep

Ceiling to top side of the blade:

261mm

Motor:

16 Pole, 153mm x 18mm motor
Made with high grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Weight Including Packaging:

Complete fan: 8.12kg

Packaging Dimensions (mm):

Complete Fan: 605L x 288W x 295H

Motor Housing:

Materials: Die Cast Aluminium

Accessories (Supplied separately):

Remote Control
Extension Down Rod 26mm diameter (includes wire harness)
38° Ceiling Kit (for pitched ceilings)
T-Hook for ceiling roses

Available Motor Housing Colours :

White, Brushed Aluminium and Matt Black

Blades:

Sizes: 1320mm (52")
Materials: Plywood Timber Blades
Blade Pitch: 12°

Warranty

2 years standard warranty "in home"
3 years extended warranty on motor only (excluding labour)

Available Blade Colours:

White, Silver and Matt Black

Extra Information:

Introduced into the HPI range in 2017
3 Speed wall controller
Reversible
Light Adaptable

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

	HIGH	MED	LOW
RPMS	188	125	82
WATTS	58.5	25	13
AIRFLOW: CFM* / CMH*	7500 / 12745	4507 / 7656	2253 / 3828
EFFICIENCY[^]: (CFM / Watt) / (CMH / Watt)	128 / 218	180 / 306	173 / 294

* CFM = Cubic Feet per Minute / CMH = Cubic Meters per Hour.

[^] Efficiency measured as airflow rate per Watt.

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au