AQUA IP66 CEILING FAN



Installation Locations: IP66 certified Indoor, outdoor and coastal locations

Recommended Height: There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan: Approximately 300mm

Motor:

158mm x 10mm DC motor Made with high grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Top Canopy & Downrod: Materials: ABS Polymer & Aluminium

Available Colours: Matt White and Matt Black

Blades:

Sizes: 1320mm (52") Materials: ABS Polymer Blade Pitch: 13.5°

Available Blade Colours: Matt White and Matt Black

Extra Information: Introduced into the HPI range in 2019 6 Speed remote controller Reversible Matt Black with Matt Black Blade

Standard Canopy Cover: Suitable for flat ceiling

Wall Controller Speed Capacitor Values: N/A

Rotational Diameter: 1320mm (52") blade sweep

Ceiling to top side of the blade: Approximately 270mm

Weight Including Packaging: Complete fan: 6.3kg

Packaging Dimensions (cm): Complete Fan: 69L x 30W x 26.8H

Accessories (Supplied separately): Extension Threaded Down Rod 26mm diameter T-Hook for ceiling roses

Warranty

2 years in-home warranty on all electric components (control modules, remote control system, lighting and accessory wall control) 3 years standard "in home" warranty 3 years extended warranty on motor only (excluding labour)

Airflow CMH: 14,286 on High speed (Speed 6)

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

	Speed 1	Speed 2	Speed 3	Speed 4	Speed 5	Speed 6
RPMS	73	105	154	168	180	193
WATTS	2	4	9	12	16	19

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au