

LED 3528 STRIP KITS IP65 (2M & 5M)





PRODUCT SPECIFICATIONS

• Input voltage: 12V DC

• SMD3528 LED chips (60pcs per meter)


• Power factor: ≥0.05 • Life time: 20,000hrs

• Dimensions: W 8mm x D 2mm

• 3M tape

• Beam angle: 120°

- Not suitable for dimming
- 2 year replacement warranty





NOTE:

- Tail connector & LED driver IP20 only
- Not suitable for diffused channels
- Installation surface must be smooth, clean and dry
- The LED strip can not be joined
- Strip can be cut at the cutting lines
- Strip not suitable for going around corners

IP20	IP20				IP65																
LED DRIVER	12V DC	Male Female JOINER PLUG	=0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Part No.	LED QTY		Total Power	CRI	Lumens	Current	Package	Dimensions	
2M3K352860IP65	120pcs	3000K	9.6W	>80	800lm	1.0A	2m/reel	2000x8x2mm	
2M5K352860IP65	120pcs	5000K	9.6W	>80	850lm	1.0A	2m/reel	2000x8x2mm	
5M3K352860IP65	300pcs	3000K	24W	>80	2000lm	2.0A	5m/reel	5000x8x2mm	
5M5K352860IP65	300pcs	5000K	24W	>80	2120lm	2.0A	5m/reel	5000x8x2mm	

UPDATED ON 02.05.2017

Tel: (02) 9938 7100 | **Fax:** (02) 9938 7115 | **Email:** sales@clalighting.com.au Follow us: facebook.com/CLALighting Website: www.clalighting.com.au

