

SLICK SERIES: LED Slim Downlights



PRODUCT FEATURES

- Input voltage: 240V AC 50-60Hz
- Wattage: 9W, 12W & 18W
- SMD2835 LED chips
- Life time: 30,000hrs
- Power factor: 0.9
- Material: PC
- Flex & plug included
- Suitable for dimming
- Ambient temperature: -20 to 40°C
- IP20 for indoor use
- 5 year domestic & 3 year commercial warranty

CODE	DESCRIPTION	KELVIN	LUMENS (LM)	WATT (W)	CRI	BEAM (°)	DIAM. (mm)	DEPTH (mm)	CUT OUT (mm)	CARTON QTY
SLICK-R1	9W SLIM WH FIXED RND LED D/L 3000K DIMM	3000K	700	9	82	160	Ø150	22	Ø130	1/20
SLICK-R2	9W SLIM WH FIXED RND LED D/L 5000K DIMM	5000K	800	9	82	160	Ø150	22	Ø130	1/20
SLICK-R3	12W SLIM WH FIXED RND LED D/L 3000K DIMM	3000K	1000	12	82	160	Ø175	22	Ø155	1/20
SLICK-R4	12W SLIM WH FIXED RND LED D/L 5000K DIMM	5000K	1100	12	82	160	Ø175	22	Ø155	1/20
SLICK-R5	18W SLIM WH FIXED RND LED D/L 3000K DIMM	3000K	1500	18	82	160	Ø222	22	Ø205	1/20
SLICK-R6	18W SLIM WH FIXED RND LED D/L 5000K DIMM	5000K	1600	18	82	160	Ø222	22	Ø205	1/20
SLICK-S1	9W SLIM WH SQ FIXED LED D/L 3000K DIMM	3000K	700	9	82	160	150	22	130x130	1/20
SLICK-S2	9W SLIM WH SQ FIXED LED D/L 5000K DIMM	5000K	800	9	82	160	150	22	130x130	1/20
SLICK-S3	12W SLIM WH SQ FIXED LED D/L 3000K DIMM	3000K	1000	12	82	160	175	22	155x155	1/20
SLICK-S4	12W SLIM WH SQ FIXED LED D/L 5000K DIMM	5000K	1100	12	82	160	175	22	155x155	1/20
SLICK-S5	18W SLIM WH SQ FIXED LED D/L 3000K DIMM	3000K	1500	18	82	160	222	22	205x205	1/20
SLICK-S6	18W SLIM WH SQ FIXED LED D/L 5000K DIMM	5000K	1600	18	82	160	222	22	205x205	1/20

Recommended dimmers:

• CLA LYNX • CLIPSAL 32E450UDM • CLIPSAL 32E450TM • HPM CAT400T

UPDATED ON 29.11.2016

