

SURFACE MOUNT



RECESSED



240V 50Hz	8W TOTAL WATTAGE	6W NON-MTD LAMP	SMD LED	RECYCLABLE	CRI >80	Ta 40°C	D63	70-130mm	AS/NZS APPROVED
--------------	------------------------	-----------------------	---------	------------	------------	------------	-----	----------	--------------------

6W Pathfinder Emergency downlight is a general purpose, non-maintained LED emergency luminaire with D63/D63 classification, compliant to AS/NZS2293.

The Pathfinder luminaire incorporates an integral emergency 2 hour battery pack that permits self-powered operation during power outages

FEATURES

- Compliant to AS/NZS 2293
- Energy efficient high output 6 watt LED
- 2-Pin flex & plug included
- Recessed or ceiling surface mount options available
- Injection moulded polycarbonate housing
- Removeable large trim ring included
- D63/D63 classification
- High density storage LiCoO₂ batteries
- IP20 rating
- 2 Hour duration period
- TA40 - maximum thermal ambient operating temperature
- Charger type: Trickle
- Charger time: 16 Hours
- Charger operation: Continuous
- Cutout: 70 to 130mm

APPLICATIONS

Commercial and interior applications, coastal environment, apartments, shopping centres, hospitality, prisons and hospitals.

CLASSIFICATION & SPACING DISTANCE

		Mounting Height in Metres									
Plane	Class	2.1	2.4	2.7	3.0	3.6	4.0	4.5	5.0	6.0	
C0	D63	19.4	20.3	21.1	21.8	22.4	23.0	23.7	24.5	25.2	
C90	D63	19.4	20.3	21.1	21.8	22.4	23.0	23.7	24.5	25.2	

MODEL NO.	MOUNT TYPE	NON-MAINTAINED LAMP WATTAGE (W)	FITTING COLOUR
19884/..	RECESSED	6	/05-WHITE
19888/..	SURFACE	6	/05-WHITE
19895/..	SURFACE MOUNT BOX ONLY		/05-WHITE

