



# SOLARIS

## EMERGENCY LED OYSTER



240V 50Hz	28W 1400lm	6W SUSTAIN LAMP	SMD LED	5000K NATURAL WHITE		CRI >80	D32	AS/NZS APPROVED
--------------	---------------	-----------------------	---------	---------------------------	--	------------	-----	--------------------

The Solaris 28W + 6W (192 lumen) Emergency light is a general purpose, sustained mode operated ceiling luminaire. The Solaris luminaire incorporates an emergency 3 hour battery pack that permits self-powered operation during power outages.

### FEATURES

- Compliant to AS/NZS 2293
- Big bore terminal block.
- Energy efficient high output 28 watt LED
- Ceiling surface mount
- Metal base with Opal acrylic diffuser
- D32/D32 classification
- High density storage LiCoO<sub>2</sub> (3700mAh) batteries
- 3 Hour duration period
- Charger type: Trickle
- Charger time: 16 Hours
- Charger operation: Continuous

### APPLICATIONS

Commercial and interior applications, apartments, shopping centres, hospitality and hospitals.

### CLASSIFICATION & SPACING DISTANCE

		Mounting Height in Metres									
Plane	Class	2.1	2.4	2.7	3.0	3.6	4.0	4.5	5.0	6.0	
C0	D32	15.4	16.1	16.7	17.2	18.0	18.5	19.1	19.5	20.2	
C90	D32	15.4	16.1	16.7	17.2	18.0	18.5	19.1	19.5	20.2	

MODEL NO.	PRODUCT	FITTING COLOUR
19892/05	EMERGENCY MODEL	WHITE

